

Regalis I RGB Colour Mixing LED Wall Washer

Product Codes: 300mm: REG1-3 RGB | 600mm: REG1-6 RGB | 900mm: REG1-9 RGB | 1200mm: REG1-12 RGB



Key Features

- Colour Changing RGB LEDs
- Robust Extruded and Anodised Aluminium Housing
- Water Resistant to IP66
- Easily Installed
- DMX Controllable

Product Description

Surelight's Regalis RGB LED Wall Washers are fully water resistant robust LED wall washers/strip lights.

The Regalis RGB LED housings are made from corrosion resistant extruded aluminium making the Regalis extremely robust and hard wearing. Easily installed and adjustable the Regalis RGB LED Wall Washers units can be mounted to walls, floors or ceilings.

Available with a range of plastic diffusers to further light output flexibility. Ideally suited to architectural lighting, cove lighting, landscape lighting, garden lighting, facade lighting, theatres, bridges, hotels, shopping centres, bars and night clubs. Also available in a range of single colours.

Specification

Lighting Performance

Product Code	Model	LED Qty	Lumen Output	Minimum Lifetime
REG1-3 RGB	300mm	12	Red: 72lm Green: 144lm Blue: 48lm	30,000hrs
REG1-6 RGB	600mm	24	Red: 144lm Green: 288lm Blue: 96lm	30,000hrs
REG1-9 RGB	900mm	36	Red: 216lm Green: 432lm Blue: 144lm	30,000hrs
REG1-12 RGB	1200mm	48	Red: 288lm Green: 576lm Blue: 192lm	30,000hrs

Operating Details

Product Code	Model	Input Power	Input Voltage	Working Temperature Range
REG1-3 RGB	300mm	3W	24V DC	-15 to +50 °C
REG1-6 RGB	600mm	6W	24V DC	-15 to +50 °C
REG1-9 RGB	900mm	9W	24V DC	-15 to +50 °C
REG1-12 RGB	1200mm	12W	24V DC	-15 to +50 °C

Options

Optics	Diffusers	Length
120°	Transparent, Semi-Transparent, Diffused	300, 600, 900 or 1200mm

Physical Details

Product Code	Model	Mounting Type	Finish	Weight	Ingress Protection
REG1-3 RGB	300mm	Adjustable Stainless Steel Bracket	Anodised Aluminium	400g	IP66
REG1-6 RGB	600mm	Adjustable Stainless Steel Bracket	Anodised Aluminium	700g	IP66
REG1-9 RGB	900mm	Adjustable Stainless Steel Bracket	Anodised Aluminium	1000g	IP66
REG1-12 RGB	1200mm	Adjustable Stainless Steel Bracket	Anodised Aluminium	1300g	IP66

Colour



RGB

Optics



120°

Diffuser Options



Transparent Semi-Transparent Diffused Milky