


# Regalis Single Colour Mixing LED Wall Washer

Product Codes: 300mm: REG1-3 | 600mm: REG1-6 | 900mm: REG1-9 | 1200mm: REG1-12



## Key Features

- Single Colour 5050 LEDs
- Robust Extruded and Anodised Aluminium Housing
- Water Resistant to IP66 
- Easily Installed
- DMX Controllable

## Product Description

Surelight's Regalis LED Wall Washers are fully water resistant robust LED wall washers/strip lights.

The Regalis LED housings are made from corrosion resistant extruded aluminium making the Regalis extremely robust and hard wearing. Easily installed and adjustable the Regalis LED Wall Washers units can be mounted to walls, floors or ceilings.

Available with a range of plastic diffusers to further light output flexibility. Ideally suited to architectural lighting, cove lighting, landscape lighting, garden lighting, facade lighting, theatres, bridges, hotels, shopping centres, bars and night clubs.

Available in a range of single colours

## Specification

### Lighting Performance

| Product Code | Model  | LED Qty | Lumen Output | Minimum Lifetime |
|--------------|--------|---------|--------------|------------------|
| REG1-3       | 300mm  | 12      | 300lm        | 30,000hrs        |
| REG1-6       | 600mm  | 24      | 600lm        | 30,000hrs        |
| REG1-9       | 900mm  | 36      | 900lm        | 30,000hrs        |
| REG1-12      | 1200mm | 48      | 1200lm       | 30,000hrs        |

### Operating Details

| Product Code | Model  | Input Power | Input Voltage | Working Temperature Range |
|--------------|--------|-------------|---------------|---------------------------|
| REG1-3       | 300mm  | 3W          | 24V DC        | -15 to +50 °C             |
| REG1-6       | 600mm  | 6W          | 24V DC        | -15 to +50 °C             |
| REG1-9       | 900mm  | 9W          | 24V DC        | -15 to +50 °C             |
| REG1-12      | 1200mm | 12W         | 24V DC        | -15 to +50 °C             |

### Physical Details

| Product Code | Model  | Mounting Type                      | Finish             | Weight | Ingress Protection |
|--------------|--------|------------------------------------|--------------------|--------|--------------------|
| REG1-3       | 300mm  | Adjustable Stainless Steel Bracket | Anodised Aluminium | 400g   | IP66               |
| REG1-6       | 600mm  | Adjustable Stainless Steel Bracket | Anodised Aluminium | 700g   | IP66               |
| REG1-9       | 900mm  | Adjustable Stainless Steel Bracket | Anodised Aluminium | 1Kg    | IP66               |
| REG1-12      | 1200mm | Adjustable Stainless Steel Bracket | Anodised Aluminium | 1.3Kg  | IP66               |

### Options

| Optics | Diffusers                               | Length                  | Single LED Colours   |
|--------|---|-------------------------|--|
| 120°   | Transparent, Semi-Transparent, Diffused | 300, 600, 900 or 1200mm | Red, Green, Blue, Amber, Cool White, Neutral White, Warm White |

### Colour



### Optics



### Diffuser Options

