Oceanus-18 Single Colour LED Spot Lights

Product Code:OC18-SC





Key Features

Vandal-resistant 8mm tempered glass
front

• Powered by ProLight Opto LED's

Water Resistant to IP66

Tough & durable powder coated diecast aluminium housing

Product Description

The Oceanus-18 LED Spotlight is a single colour flood/spotlight which is fully water and dust resistant to IP66 rating, making the Oceanus-18 LED Spotlight perfect in any indoor or outdoor venue.

The fully adjustable and lockable bracket ensures easy mounting on most surfaces.

Available in various colour combinations the Oceanus-18 LED Spotlight can create any mood or effect you desire. External DMX decoders and LED controllers are available

Specification

ighting Perf	Operating Details										
LED Qty	Lumen Output	CRI	CRI Minimum Lifetime		Input Power				Working Temperature Range		
18 x 1.5W PM2B	2250lm >80		30,000hrs	27W				-15 to +50 °C			
Input Data				Options	5						
Input Voltage	Input Voltage Power Su		Input Connection	Optics				LED Colour			
24V DC	Constant V	oltage Drive	Flying Leads	15°, 25°, 45°, 60°, 120°				Red, Green, Blue, Amber, Warm White, Neutral White, Pure White			
Physical Deta	ils			Colour					,		
Mounting Type	Fir	nish	Ingress Protection	coroar							
Bracket mounting t walls/floors/ceiling		er coated with steel bezel	IP66								
				R	G	В	Α	WW	NW	PW	
				Optics							

15°

25°

45°

60°

120°