Atlas LED Light Fixture

Product Code: 35W - 814-0005, 45W - 814-0009, 70W - 814-0010



Key Features

Alternative to fluorescent tube fixtures.

• Water Resistant to IP65.

• Vandal Resistant to IK7.

• High power efficiency > 90%.

• Instant on, no flicker or buzz.

• No mercury allowing for nonhazardous waste disposal.

• Anti-corrosion aluminium.

· Emits virtually no UV rays or IR.

• Energy saving and environmentally friendly.

Specification

Lighting Performance

5						
Product Code	Power	LED Qty	CRI	Power Factor	Lumen Output	Minimum Lifetime
814-0005	35W	72	80	> 0.9	2280lm	30,000hrs
814-0009	45W	96	80	> 0.9	3160lm	30,000hrs
814-0010	70W	144	80	> 0.9	4600lm	30,000hrs
N B Lumen valu	ies quoted o	n Pure Wh	ite (5665-635	(0k)		

Input Data

				Colour	
Input Voltage		Power Supply Type	Input Connection		
100-240V AC		Constant Current AC	Flying Leads		
hysical I	Details			ww	
Finish	Beam Angle	Mounting	Ingress Protection	~~~~	
Aluminium	120°	Pendant or ceiling mounting	g IP65		

Product Description

The Atlas LED lighting fixture is a water resistant dust proof and anti-corrosion LED light fixture.

Designed to stand up to extreme environments the Atlas LED light fixture can be used in food processing/preparation factories as it is easily washed down. The Atlas range is water resistant and made from anti-corrosion aluminium making the Atlas range light-weight and robust.

Available in a range of brightnesses and white colours.

Operating Details

Options

Storage Temperature

-40 to +80 °C

Input Power 35W, 45W or 70W

Applications include, factories, multistory car parks, offices, retail premises, hotels, restaurants, health sector buildings, modern new build properties, libraries and public service buildings.

Working Temperature Range

-20 to +40 °C

LED Colours

Neutral White, Pure White

Optics